



CUSTOM COATINGS SYSTEMS

112 RAILROAD ST., REVERE, MA 02151

(800) 420-0021; (781) 289-1400; (781) 289-1405 (FAX)

www.durantcorp.com

DUR-A-PLEX 100

INTERIOR LATEX PRIMER

Product Number:	DUR-A-PLEX 100	Average Dry Time at 75°F(24°C):	2 hrs for 2 nd coat application
Description:	Interior Latex Primer House Paint designed as a spot primer or as an overall primer for new or repainting of residential, commercial and light industrial applications.	Reducer:	Water
Suggested Use:	Use on interior drywall, cured plaster, wood, and primed metal. Designed to prepare substrate to ensure most consistent and best performance from topcoat.	Suggested Clean Up:	Water
Colors:	White	Application:	Brush, Roller or Spray
Finish:	Low Sheen / Flat	NOTE: Do not apply if material, substrate or ambient temperature is below 45°F(7°C) or above 95°F(35°C). Best if relative humidity is below 80%.	
Vehicle Type:	Acrylic Latex	Surface Preparation:	Remove all loose dirt, rust, oil, grease, excess moisture and other foreign matter.
Solvent Type:	Water	Shelf Life:	12 months
VOC:	99 g/l (.83 #/gal)	Mixing:	Stir until thoroughly homogenized
Flash Point:	N/A	Caution:	Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator
Solids by Volume:	49.6 %		
Weight per Gallon :	12.0 lbs.		
Recommended Dry Film:	2.5-3.0 dry mil		
Coverage:	Theoretical coverage at one mil dry = 635 square feet (estimate does not include normal material losses during mixing and application process).		
Viscosity at 75°F(24°C):	85-95 KU		

manufacturer's directions for eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

respirator use. Avoid contact with

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF THE REACH OF
CHILDREN.**

Packaging: 1 Gallon Cans (4 per case)
5 Gallon Pails

The Information and recommendations contained in this Product Data Sheet are based upon tests conducted by or on behalf of Durant Corp. and are accurate to the best of our knowledge. The information and recommendations contained herein are subject to change. Workmanship, weather, equipment, quality of other materials used or other variables may affect results. Contact Durant Corp. with any questions or comments.