

DURANT

PERFORMANCE COATINGS

112 RAILROAD ST., REVERE, MA 02151

(800) 420-0021; (781) 289-1400; (781) 289-1405 (FAX)

www.durantcorp.com

DUR-A-PLEX Ultra 1100

EXTERIOR LATEX SEMI-GLOSS [Conforms to Master Painter Institute #11 Specifications]

Product Number:	DUR-A-PLEX Ultra 1100	at 75°F(24°C):	2 hrs for 2 nd coat application
Description:	Exterior Latex Semi-Gloss House Paint with excellent hiding and weathering properties.	Reducer:	Water
Suggested Use:	Use on exterior primed metals and wood, stucco or masonry surfaces. Recommended for trim, fascia and smooth surfaces.	Suggested Clean Up:	Water
Colors:	White & Custom Colors	Application:	Brush, Roller or Spray
Finish:	Semi-Gloss		NOTE: Do not apply if material, substrate or ambient temperature is below 45°F(7°C) or above 95°F(35°C). Best if relative humidity is below 80%.
Vehicle Type:	Acrylic Latex	Surface Preparation:	Remove all loose dirt, rust, oil, grease, excess moisture and other foreign matter.
Solvent Type:	Water		
VOC:	~136 g/l (1.13 #/gal)	Shelf Life:	12 months
Flash Point:	N/A	Mixing:	Stir until thoroughly homogenized
Solids by Volume:	31.8 %	Caution:	Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with
Weight per Gallon :	10.44 lbs.		
Recommended Dry Film:	2.5-3.0 dry mil		
Coverage:	Theoretical coverage at one mil dry = 635 square feet (estimate does not include normal material losses during mixing and application process).		
Viscosity at 75°F(24°C):	85-95 KU		
Average Dry Time			

eyes and skin. Wash hands after using.
Keep container closed when not in use.
Do not transfer contents to other
containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF THE REACH OF
CHILDREN.**

Packaging: 1 Gallon Cans (4 per case)
5 Gallon Pails

The Information and recommendations contained in this Product Data Sheet are based upon tests conducted by or on behalf of Durant Performance Coatings, Inc. and are accurate to the best of our knowledge. The information and recommendations contained herein are subject to change. Workmanship, weather, equipment, quality of other materials used or other variables may affect results. Contact Durant Performance Coatings, Inc. with any questions or comments.