



CUSTOM COATINGS SYSTEMS

112 RAILROAD ST., REVERE, MA 02151
(800) 420-0021; (781) 289-1400; (781) 289-1405 (FAX)
www.durantcorp.com

DUR-A-PLEX 1190
INTERIOR / EXTERIOR ACRYLIC LATEX GLOSS

Table with 4 columns: Property, Value, Property, Value. Rows include Product Number, Description, Suggested Use, Colors, Finish, Vehicle Type, Solvent Type, VOC, Flash Point, Solids by Volume, Weight per Gallon, Recommended Dry Film, Coverage, Viscosity, and Average Dry Time.

not in use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF THE REACH OF
CHILDREN.**

Packaging: 1 Gallon Cans (4 per case)
5 Gallon Pails

The Information and recommendations contained in this Product Data Sheet are based upon tests conducted by or on behalf of Durant Corp. and are accurate to the best of our knowledge. The information and recommendations contained herein are subject to change. Workmanship, weather, equipment, quality of other materials used or other variables may affect results.