

DURANT

PERFORMANCE COATINGS

112 RAILROAD ST., REVERE, MA 02151

(800) 420-0021; (781) 289-1400; (781) 289-1405 (FAX)

www.durantcorp.com

DUR-A-PLEX Ultra 1380

HIGH PERFORMANCE ARCHITECTURAL LATEX - Eggshell

[Conforms to Master Painter Institute #138 Specifications]

Product Number:	DUR-A-PLEX Ultra 1380	Average Dry Time at 75°F(24°C):	2 hrs for 2 nd coat application
Description:	Interior High Performance Architectural Latex, Eggshell Finish. 10 unit Gloss reading at 60 degrees.	Reducer:	Water
Suggested Use:	Recommended for use on interior previously painted or primed wood, metal or drywall surfaces. Designed to provide a high level of performance in the areas of scrub resistance and ease of stain removal.	Suggested Clean Up:	Water
Colors:	White & Custom Colors	Application:	Brush, Roller or Spray
Finish:	Eggshell Sheen	NOTE:	Do not apply if material, substrate or ambient temperature is below 45°F(7°C) or above 95°F(35°C). Best if relative humidity is below 80%.
Vehicle Type:	Acrylic Latex	Surface Preparation:	Remove all loose dirt, rust, oil, grease, excess moisture and other foreign matter.
Solvent Type:	Water	Shelf Life:	12 months
VOC:	105 g/l (.87 #/gal)	Mixing:	Stir until thoroughly homogenized
Flash Point:	N/A	Caution:	Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator
Solids by Volume:	37.3 %		
Weight per Gallon :	11.34 lbs.		
Recommended Dry Film:	2.5-3.0 dry mil		
Coverage:	Theoretical coverage at one mil dry = 598 square feet (estimate does not include normal material losses during mixing and application process).		
Viscosity at 75°F(24°C):	85-95 KU		

manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF THE REACH OF
CHILDREN.**

Packaging: 1 Gallon Cans (4 per case)
5 Gallon Pails

The Information and recommendations contained in this Product Data Sheet are based upon tests conducted by or on behalf of Durant Performance Coatings, Inc., and are accurate to the best of our knowledge. The information and recommendations contained herein are subject to change. Workmanship, weather, equipment, quality of other materials used or other variables may affect results. Contact Durant Performance Coatings, Inc., with any questions or comments.