

MATERIAL SAFETY DATA SHEET

DUR-A-PLEX 1380 / Ultra 1380

Revised: 9/10/07 Page 1

----- HMIS CODES -----

Hazard Rating: Health 1
Least --> Greatest Flammability 0
Manufacturer: 0 --> 4 Reactivity 0
DURANT PERFORMANCE COATINGS, INC. Personal Protection B
112 Railroad St.
Revere, MA 02151
Phone: 781-289-1400

EMERGENCY TELEPHONE: 800-424-9300

----- SECTION I: PRODUCT IDENTIFICATION -----

Product Code: DUR-A-PLEX 1380 / Ultra 1380 Interior Eggshell
Color: Applies to All Colors Chemical Name/Class: LATEX PAINT
CAS Number: NONE NSN #: See Attached

----- SECTION IIA: HAZARDOUS INGREDIENTS -----

Table with 6 columns: Ingredient, CAS Number, % by Wt., % by Vol., LEL, Vapor Press. Includes entries for PROPYLENE GLYCOL and OXYGENATED HYDROCARBON.

----- SECTION IIB: OCCUPATIONAL EXPOSURE LIMITS -----

Table with 7 columns: Ingr. #, OSHA ppm, OSHA mg/m3, TWA ppm, TWA mg/m3, STEL ppm, STEL mg/m3. Includes entries for OSHA PEL's and ACGIH TLV's.

OSHA: Na
ACGIH: Na

NA = Not Applicable; NE = Not Established

----- SECTION III: PHYSICAL DATA -----

Boiling Range (degrees F): 212.00 - 270.00 Pounds per Gallon: 11.34
Vapor Density: HEAVIER THAN AIR Evaporation Rate: SLOWER THAN ETHER
Solubility in Water: 100

Table with 3 columns: Volatiles (%), by Weight, by Volume. Includes sub-rows for Total, Exempt VOC, and Non-exempt.

VOC wt/gal: .87 lbs non-exempt solvent per adjusted gallon (105gm/L)
Appearance: OPAQUE LIQUID

----- SECTION IV: FIRE AND EXPLOSION HAZARD DATA -----

Flammability Classification:
OSHA: NON-FLAMMABLE DOT: NON-FLAMMABLE
Flash Point: NA (Method:)

Extinguishing Media: CO2/WATER

Unusual Fire and Explosion Hazards
COOL CONTAINERS WITH WATER STREAM IN THE EVENT OF FIRE.

Special Firefighting Procedures
DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL PROTECTIVE GEAR.

SECTION V: HEALTH HAZARD DATA

Effects of Overexposure

EYES - LIQUID OR VAPOR CONTACT MAY CAUSE EYE IRRITATION.
 SKIN - BRIEF CONTACT CAN BE MILDLY IRRITATING. AVOID EXCESSIVE CONTACT.
 INHALATION - VAPORS CAN BE IRRITATING TO NOSE AND THROAT. SYMPTOMS OF OVEREXPOSURE MAY INCLUDE HEADACHE, NAUSEA, VOMITING, DROWSINESS.
 INGESTION - SLIGHTLY TOXIC

Medical Conditions Prone to Aggravation by Exposure
 HEART CONDITIONS, ASTHMA

Primary Routes of Entry into the Body, and Effects
 INHALATION, DERMAL CONTACT, EYE CONTACT, INGESTION.

EMERGENCY FIRST-AID PROCEDURES

EYES - FLUSH WITH WATER FOR 15 MINUTES.
 SKIN - WASH WITH SOAP AND WATER, REMOVE CONTAMINATED CLOTHING.
 INHALATION - REMOVE TO FRESH AIR. PROVIDE OXYGEN IF BREATHING IS DIFFICULT.
 INGESTION - DO NOT GIVE LIQUIDS IF UNCONSCIOUS. OTHERWISE, GIVE NO MORE THAN 2 GLASSES OF WATER AND INDUCE VOMITING.

SECTION VI: REACTIVITY DATA

Stability: STABLE Hazardous Polymerization Conditions to Avoid: HEAT, SPARKS AND
 WILL NOT OCCUR. OPEN FLAMES.

Hazardous Decomposition Products: NONE Incompatibilities (Materials to Avoid)

SECTION VII: SPILL OR LEAK PROCEDURES; WASTE DISPOSAL

Steps to be taken if Material is Leaked or Spilled
 DIKE AND CONTAIN LIQUID. SOAK UP RESIDUE WITH ABSORBENT MATERIAL.

Waste Disposal Methods
 DISPOSE OF IN APPROVED FACILITY

SECTION VIII: SAFE HANDLING AND USE INFORMATION

Respiratory Protection: YES
 Ventilation: YES
 Protective Gloves: YES
 Eye Protection: YES
 Other Protective Equipment: APRON
 Hygienic Practices: WASH HANDS AFTER HANDLING, WITH SOAP AND WATER

SECTION IX: SPECIAL PRECAUTIONS

Handling and Storing
 STORE IN COOL DRY PLACE. PROTECT PRODUCT FROM FREEZING.
 Other Precautions

NATIONAL STOCK NUMBERS (NSN):

8010-00-045-3478	8010-00-579-9530	8010-00-584-3356	8010-00-598-5744
8010-00-291-0599	8010-00-579-9531	8010-00-584-3357	8010-00-838-7116
8010-00-291-0601	8010-00-579-9533	8010-00-584-3358	8010-00-901-8081
8010-00-463-7063	8010-00-584-3136	8010-00-598-5726	8010-00-901-8082
8010-00-527-2407	8010-00-584-3137	8010-00-598-5730	8010-00-901-8083
8010-00-527-2494	8010-00-584-3140	8010-00-598-5733	8010-00-901-8085
8010-00-527-2620	8010-00-584-3141	8010-00-598-5735	8010-01-018-2927
8010-00-530-4690	8010-00-584-3145	8010-00-598-5736	
8010-00-579-9199	8010-00-584-3147	8010-00-598-5737	
8010-00-579-9202	8010-00-584-3353	8010-00-598-5738	

END OF MSDS