

MATERIAL SAFETY DATA SHEET

DUR-A-PLEX 200 EXTERIOR LATEX PRIMER

Revised: 1/11/07 Page 1

 ----- HMIS CODES -----
 Hazard Rating: Health 1
 Least --> Greatest Flammability 0
 0 --> 4 Reactivity 0
 Personal Protection B
 Manufacturer: DURANT PERFORMANCE COATINGS, INC.
 112 RAILROAD STREET
 REVERE, MA 02051
 Phone: 800-420-0021 EMERGENCY TELEPHONE: 800-424-9300

SECTION I: PRODUCT IDENTIFICATION

Product Code: DUR-A-PLEX 200 EXTERIOR LATEX PRIMER
 Chemical Name/Class: LATEX PAINT CAS Number: NONE

SECTION IIA: HAZARDOUS INGREDIENTS
 (To Nearest .10%)

Ingredient	CAS Number	% by Wt.	% by Vol.	LEL	Vapor Press.
1. PROPYLENE GLYCOL	57-55-6	1.60	2.30	NA	NA
2. OXYGENATED HYDROCARBON	25265-77-4	1.40	2.20	.6	1.00

NA = Not Applicable; NE = Not Established

SECTION IIB: OCCUPATIONAL EXPOSURE LIMITS

Ingr. #	-----OSHA PEL's-----			-----ACGIH TLV's-----		
	OSHA ppm	OSHA mg/m3	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3
1.	NA	NA	NA	NA	NA	NA
2.	NE	NE	NE	NE	NE	NE

OSHA: Na
 ACGIH: Na

NA = Not Applicable; NE = Not Established

SECTION III: PHYSICAL DATA

Boiling Range (degrees F): 212.00 - 470 Pounds per Gallon: 12
 Vapor Density: HEAVIER THAN AIR Evaporation Rate: SLOWER THAN ETHER
 Solubility in Water: 100

Volatiles (%)	by Weight		by Volume
	Total	Exempt VOC	Non-exempt
	37.9	34.4	54.2
		3.5	4.6

VOC wt/gal: .83 lbs non-exempt solvent per adjusted gallon
 Appearance: OPAQUE LIQUID

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

Flammability Classification:
 OSHA: NON-FLAMMABLE DOT: NON-FLAMMABLE
 Flash Point: NA (Method:)

Extinguishing Media: CO2/WATER

Unusual Fire and Explosion Hazards
 COOL CONTAINERS WITH WATER STREAM IN THE EVENT OF FIRE.

Special Firefighting Procedures
 DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL PROTECTIVE GEAR.

SECTION V: HEALTH HAZARD DATA

Effects of Overexposure

EYES - LIQUID OR VAPOR CONTACT MAY CAUSE EYE IRRITATION.
SKIN - BRIEF CONTACT CAN BE MILDLY IRRITATING. AVOID EXCESSIVE CONTACT.
INHALATION - VAPORS CAN BE IRRITATING TO NOSE AND THROAT. SYMPTOMS OF
OVEREXPOSURE MAY INCLUDE HEADACHE, NAUSEA, VOMITING, DROWSINESS.
INGESTION - SLIGHTLY TOXIC

Medical Conditions Prone to Aggravation by Exposure
HEART CONDITIONS, ASTHMA

Primary Routes of Entry into the Body, and Effects
INHALATION, DERMAL CONTACT, EYE CONTACT, INGESTION.

EMERGENCY FIRST-AID PROCEDURES

EYES - FLUSH WITH WATER FOR 15 MINUTES.
SKIN - WASH WITH SOAP AND WATER, REMOVE CONTAMINATED CLOTHING.
INHALATION - REMOVE TO FRESH AIR. PROVIDE OXYGEN IF BREATHING IS DIFFICULT.
INGESTION - DO NOT GIVE LIQUIDS IF UNCONSCIOUS. OTHERWISE, GIVE NO MORE THAN
2 GLASSES OF WATER AND INDUCE VOMITING.

SECTION VI: REACTIVITY DATA

Stability: STABLE Hazardous Polymerization WILL NOT OCCUR.

Hazardous Decomposition Products: NONE

Conditions to Avoid: HEAT, SPARKS AND OPEN FLAMES.

Incompatibilities (Materials to Avoid)

SECTION VII: SPILL OR LEAK PROCEDURES; WASTE DISPOSAL

Steps to be taken if Material is Leaked or Spilled
DIKE AND CONTAIN LIQUID. SOAK UP RESIDUE WITH ABSORBENT MATERIAL.

Waste Disposal Methods: DISPOSE OF IN APPROVED FACILITY

SECTION VIII: SAFE HANDLING AND USE INFORMATION

Respiratory Protection: YES Eye Protection: YES

Ventilation: YES Other Protective Equipment: APRON

Protective Gloves: YES Hygienic Practices: WASH HANDS AFTER
HANDLING, WITH SOAP AND WATER

SECTION IX: SPECIAL PRECAUTIONS

Handling and Storing
STORE IN COOL DRY PLACE. PROTECT PRODUCT FROM FREEZING.

Other Precautions

END OF MSDS