



112 RAILROAD ST., REVERE, MA 02151
(800) 420-0021; (781) 289-1400; (781) 289-1405 (FAX)
www.durantcorp.com

DUR-A-PLEX Ultra 500

EXTERIOR ALKYD WOOD PRIMER [Conforms to Master Painter Institute #5 Specifications]

Product Number:	DUR-A-PLEX Ultra 500	Reducer:	Not Recommended due to VOC Restrictions
Description:	Exterior Alkyd Wood Primer	Suggested Clean Up:	Mineral Spirits
Suggested Use:	Basecoat designed for priming exterior wood, manufactured siding, hardboard, rough siding, and trim as a spot primer or overall primer	Application:	Brush, Roller or Spray
Colors:	White		NOTE: Do not apply if material, substrate or ambient temperature is below 45°F(7°C) or above 95°F(35°C). Best if relative humidity is below 80%.
Finish:	Flat.		
Vehicle Type:	Alkyd Resin	Surface Preparation:	Remove all loose dirt, rust, oil, grease, excess moisture and other foreign matter.
Solvent Type:	Aliphatic Hydrocarbon		
VOC:	326 g/l (2.72#/gal)	Shelf Life:	12 months
Flash Point:	103°F(39°C)	Mixing:	Stir until thoroughly homogenized.
Solids by Volume:	58.3%		
Weight per Gallon :	12.6 lbs.	Caution:	Contents are COMBUSTIBLE. Keep away from heat and open flame. VAPOR HARMFUL. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with
Recommended Dry Film:	2.5-3.0 mils		
Coverage:	Theoretical coverage at one mil dry = 935 square feet (estimate does not include normal material losses during mixing and application process).		
Viscosity at 75°F(24°C):	85-95 KU		
Average Dry Time at 75°F(24°C):	8 hrs for 2 nd coat application		

eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

Delayed Effects from Long term Overexposure. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Reports have associated repeated or prolonged overexposure to solvents with permanent brain and nervous system damage.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF THE REACH OF
CHILDREN.**

Packaging: 1 Gallon Cans (4 per case)
5 Gallon Pails

The Information and recommendations contained in this Product Data Sheet are based upon tests conducted by or on behalf of Durant Performance Coatings, Inc. and are accurate to the best of our knowledge. The information and recommendations contained herein are subject to change. Workmanship, weather, equipment, quality of other materials used or other variables may affect results. Contact Durant Performance Coatings, Inc. with any questions or comments.